

**Amendments to the Claims:** This listing of claims will replace all prior versions, and listings, of claims in the application

Listing of Claims:

Claims 1.-14. (Canceled)

15. (Original) A power-on/off reset circuit characterized by comprising a voltage detection circuit which detects a first voltage and a second voltage higher than the first voltage, and outputs a first signal, the first signal being transmitted at the second voltage when a power-supply voltage rises, and transmitted at the first voltage when the power-supply voltage drops, and a new operational sequence being prevented when the power-supply voltage is equal to or lower than a voltage for the first signal to be transmitted.

16. (Original) A power-on/off reset circuit characterized by comprising a first voltage detection circuit which detects a first voltage and a second voltage higher than the first voltage, and outputs a first signal, and a second voltage detection circuit which detects a third voltage which is lower than the first voltage and outputs a second signal, the first signal being transmitted at the second voltage when a power-supply voltage rises, and transmitted at the first voltage when the power-supply voltage drops, a new operational sequence being prevented when the power-supply voltage is equal to or lower than a voltage for the first signal to be transmitted, and an operation being immediately suspended when the power-supply voltage is equal to or lower than the third voltage.

17. (Original) A power-on/off reset circuit characterized by comprising a first voltage detection circuit which detects a first voltage detection circuit which detects a first voltage and a second voltage higher than the first voltage and outputs a first signal, and a second voltage detection circuit which detects a third voltage which is lower than the first voltage and outputs a second signal, the first signal being transmitted at the second voltage when a power-supply voltage rises and transmitted at the first voltage when the power-supply voltage drops, a time for a power-supply voltage to drop from the first voltage to the third voltage being longer than a predetermined operational sequence completion time.

18. (Canceled)

19. (Canceled)

20. (Original) A semiconductor device comprising a non-volatile memory and a power-on/off reset circuit including a voltage detection circuit which detects a first voltage and a second voltage higher than the first voltage and outputs a first signal, the first signal being transmitted at the second voltage when a power-supply voltage rises, and transmitted at the first voltage when the power-supply voltage drops, and preventing a new operational sequence when the power-supply voltage is equal to or lower than a voltage for the first signal to be transmitted, wherein

the semiconductor device is characterized by not operating the non-volatile memory when the power-supply voltage is equal to or lower than the first voltage or equal to or lower than the third voltage.

21. (Original) A semiconductor device comprising a non-volatile memory and a power-on/off reset circuit characterized by comprising a first voltage detection circuit which detects a first voltage and a second voltage higher than the first voltage and outputs a first signal, and a second voltage detection circuit which detects a third voltage which is lower than the first voltage and outputs a second signal, the first signal being transmitted at the second voltage when a power-supply voltage rises, and transmitted at the first voltage when the power-supply voltage drops, preventing a new operational sequence when a power-supply voltage is equal to or lower than the voltage for the first signal to be transmitted, and immediately suspending an operation when the power-supply voltage is equal to or lower than the third voltage, wherein

the semiconductor device is characterized by not operating the non-volatile memory when the power-supply voltage is equal to or lower than a voltage for the first signal to be transmitted or equal to or lower than the third voltage.

Respectfully submitted,

  
\_\_\_\_\_  
Allan Rather, Reg. No. 19,717  
Attorney for Applicants


AR/dlm

Dated: March 10, 2004

P.O. Box 980  
Valley Forge, PA 19482-0980  
(610) 407-0700

**EXPRESS MAIL**      Mailing Label Number:      EV 418254085 US  
                            Date of Deposit:      March 10, 2004

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

  
\_\_\_\_\_  
Kathleen Libby

DLM\_I:\MTS\2101US3\PRELIM\_AMEND.DOC